



ALUMAX

BATH ENCLOSURES

a product of Alcoa

Tel: 800-643-1514

Fax: 870-234-3181

1038 Pivot Shower Door-Frameless

www.alumaxbath.com

Product Features

Available in standard and custom configuration
 3/8 tempered safety glass (notched for rails)
 Glass jamb = 1/4 tempered glass with beveled edge
 Pivot side adjustment is $\pm 7/8$

Options

Adj. strike jamb with V-293 vinyl
 Glass patterns
 Finish

Calculations

Maximum allowable width of unit = 32 (@ 76 tall)
 Maximum allowable height of unit = 84 (@ 27 wide)

Glass Size

Width = Unit Width - 2 3/8
 Height = Unit Ht. - 2 3/8
 Jamb Glass = 3 1/2 wide x Unit ht - 1 1/2

Metal Cuts

SC-605 pivot jamb = Unit ht. - 7/16
 SC-606 strike jamb = Unit ht. - 1 1/2
 SC-607 (optional) = Unit width

1038 Parts List

- A. 1 Curb
- B. 2 Rolls of Tape (double-stick)
- C. 1 Pivot Jamb
- D. 1 Female Gravity Pivot
- E. 2 Pivot Brackets
- F. 8 #8 x 2 Flat Head Screws
- G. 1 Beveled Glass Jamb
- H. 1 Male Gravity Pivot
- J. 1 Upper Pivot Bushing
- K. 2 Pivot Blocks with Pins
- L. 2 #10 x 7/16" Square Head Set Screws
- M. 2 Door Rails
- N. 1 Glass Door
- P. 6 Vinyl Rail Shims (3 sets)
- S. 1 Vinyl Drip Deflector
- T. 1 Strike Jamb
- U. 1 Bulb Vinyl for Strike
- V. 2 Nylon Handle Bushings
- W. 2 Handle Bases (Male)
- X. 4 Rubber Handle Gaskets
- Y. 2 Handle Bases (Female)
- AA. 2 #8 x 5/8 Flat Head Screws
- BB. 2 Door Handle Assemblies
- CC. 1 Adjustable Strike Jamb Assembly
- DD. 2 Clear Stick-On Bumpers

