



ALUMAX

BATH ENCLOSURES

a product of Alcoa

Tel: 800-643-1514

Fax: 870-234-3181

300c Continuous Hinge Shower Door-Frameless

www.alumaxbath.com

Product Features

- Available in standard and custom configuration
- Tempered safety glass
- Door has a continuous extruded ball and socket hinge that is integral to the hinge rail and jamb
- Hinge assembly has a molded bushing attached at the top and bottom of door panel
- Total unit width adjustment is $\pm 5/8$

Calculations

- Maximum allowable width of unit = 37 (@ 72 tall)
- Maximum allowable height of unit = 84 (@ 30 wide)

Glass Size

- Width = Unit width - 3 5/8
- Height = Unit ht. - 2 1/16

Metal Cuts

- SC-508 wall jamb = Unit ht. - 7/16
- SC-552 strike jamb = Unit ht. - 1
- SC-558 bottom rail = Unit width - 4 1/2
- SC-589 drip rail = Bottom rail + 1 1/4
- SC-649 hinge jamb = Unit ht. - 7/16
- SC-651 hinge rail = Unit ht. - 1 9/16
- SC-915 curb = Unit width

300c Parts List

- A. 1 Shower Curb
- B. 1 Glazed Door Panel Assembly
- C. 1 Bottom Rail
- D. 2 Wall Jamb
- E. 6 Plastic Wall Anchors
- F. 6 #8 x 1 1/2 Truss Head Screws
- G. 6 #6 x 3/8 Pan Head Tex Screws
- H. 1 Strike Jamb w/Magnet
- J. 1 Pull Handle
- K. 1 Handle Vinyl
- L. 1 Drip Rail
- M. 1 Roll of Double-Stick Tape
- N. 1 Tapered Drip Vinyl
- P. 1 #6 x 3/8 Pan Head Screw
- R. 1 Set Drip Rail Plugs
- S. 1 Rail End Cap

