



ALUMAX

BATH ENCLOSURES

a product of Alcoa

Tel: 800-643-1514

Fax: 870-234-3181

600c Continuous Hinge Shower Door-Framed

www.alumaxbath.com

Product Features

- Available in standard and custom configuration
- Tempered safety glass
- Door has a continuous extruded ball and socket hinge that is integral to the hinge rail jamb
- Hinge assembly has a molded bushing attached at the top and bottom of door panel
- Adjustable hinge jamb provides $\pm 1/4$ adjustment
- Adjustable strike jamb (optional) provides $\pm 5/16$ adjustment

Calculations

- Maximum allowable width of unit = 38 (@ 72 tall)
- Maximum allowable height of unit = 84 (@ 30 wide)

Glass Size

- Width = opening - 3 11/16
- Height = Unit ht. - 2 7/8

Metal Cuts

- SC-508 wall jamb = Unit ht. + 1/8
- SC-612 deflector = Bottom rail - 3/16
- SC-649 hinge jamb = Unit ht. + 1/8
- SC-650 top & bottom rails = Unit width - 1 13/16
- SC-801 strike jamb = Unit ht. - 7/16
- SC-913 curb (optional) = Unit width
- 68199 hinge rail = Unit ht. - 1
- 68362 strike rail = Unit ht. - 1

600c Parts List

- A. 1 Curb
- B. 1 Wall Jamb
- C. 6 Plastic Wall Anchors
- D. 6 #8 x 1 1/2 Truss Head Screws
- E. 1 Glazed Door Panel
- F. 3 #8 x 1/4 Truss Head Screws
- G. 1 Strike Jamb
- H. 3 #8 x 1 1/2 Flat Head Screws
- I. 1 Interior Door Handle
- J. 1 Exterior Door Handle
- K. 2 #8 x 1 1/8 Oval Head Screws
- L. 1 Door Latch
- M. 2 #6 x 1/4 Pan Head Screws
- N. 1 Drip Deflector
- O. 1 Drip Vinyl
- P. 1 Roll of Double Stick Tape

