



ALUMAX

BATH ENCLOSURES

a product of Alcoa

Tel: 800-643-1514

Fax: 870-234-3181

700c Continuous Hinge Shower Door-Framed

www.alumaxbath.com

Product Features

Available in standard and custom configuration

Tempered safety glass

Door has a continuous extruded ball and socket hinge that is integral to the hinge rail jamb

Hinge assembly has a molded bushing attached at the top and bottom of door panel

Adjustable jambs provide + 3/8 and - 1/4 adjustment on each side of the unit

Optional towel bar kit

Calculations

Maximum allowable width of unit = 38 (@ 72 tall)

Maximum allowable height of unit = 84 (@ 30 wide)

Glass Size

Width = opening - 4 11/16

Height = Unit ht. - 3 7/16

Metal Cuts

SC-508 wall jamb = Unit ht. - 7/16

SC-549 strike rail = Unit ht. - 1 9/16

SC-552 strike jamb = Unit ht. - 7/16

SC-589 drip rail = SC-899 bottom rail - 11/16

SC-649 hinge jamb = Unit ht. - 7/16

SC-648 hinge rail = Unit ht. - 1 9/16

SC-899 top & bottom rails = Unit width - 2 13/16

SC-915 curb = Unit width

700c Parts List

- A. 1 Curb
- B. 2 Wall Jambs
- C. 6 Plastic Wall Anchors
- D. 6 #8 x 1 1/2 Truss Head Screws
- E. 1 Glazed Door Panel
- F. 1 Strike Jamb with Magnet
- G. 6 #8 x 1/4 Truss Head Screws
- H. 2 #6 x 1 1/4 Pan Head Screws
- J. 1 Interior Door Handle
- K. 1 Exterior Door Handle
- M. 1 Drip Rail
- N. 1 Tapered Drip Rail
- P. 2 Drip Plugs
- R. 1 Roll of Double Stick Tape
- S. 1 #6 x 3/8 Truss Head Screw

