



# ALUMAX

## BATH ENCLOSURES

a product of Alcoa

Tel: 800-643-1514

Fax: 870-234-3181

# 700i INTRE-Hinge Shower Door-Framed

[www.alumaxbath.com](http://www.alumaxbath.com)

## Product Features

Available in standard and custom configuration

Tempered safety glass

Door has a continuous knuckle-and-pin hinge that is integral to the hinge rail and jamb

Full height hinge pin and retaining screws are stainless steel

Adjustable jambs provide + 3/8 and - 1/4 adjustment on each side of the unit

Optional towel bar kit

## Calculations

Maximum allowable width of unit = 40 (@ 72 tall)

Maximum allowable height of unit = 96 (@ 30 wide)

## Glass Size

Width = opening - 4 5/8

Height = Unit ht. - 3 7/16

## Metal Cuts

SC-508 wall jamb = Unit ht. - 7/16

SC-549 strike rail = Unit ht. - 1 9/16

SC-552 strike Jamb = Unit ht. - 7/16

SC-612 deflector = SC-899 bottom rail - 1

SC-899 top & bottom rails = Unit width - 2 3/4

SC-913 curb (optional) = Unit width

66769 intre-hinge jamb = Unit ht. - 7/16

66842 intre-hinge rail = Unit ht. - 7/16

## 700i Parts List

- A. 1 Curb
- B. 2 Wall Jamb
- C. 6 Plastic Wall Anchors
- D. 6 #8 x 1 1/2 Truss Head Screws
- E. 1 Clear Vinyl Jamb Seal
- F. 1 Door & Hinge Jamb Assembly
- G. 1 Strike Jamb with Magnet
- H. 6 #8 x 1/4 Truss Head Screws
- J. 1 Interior Door Handle
- K. 1 Exterior Door Handle
- L. 2 #6 x 1 1/4 Round Head Screws
- M. 1 Splash Deflector
- N. 1 Clear Vinyl Wiper
- P. 1 Roll of Double Stick Tape

