



ALUMAX

BATH ENCLOSURES

a product of Alcoa

Tel: 800-643-1514

Fax: 870-234-3181

940/950 Tri-Slider Shower Door-Framed

www.alumaxbath.com

Product Features

- Available in standard and custom configuration
- Tempered safety glass
- Adjustable ball bearing rollers
- Total adjustment of panels is .250
- Triple panel design results in greater accessibility to tub or shower

Options

- Wall fill
- Curb fill
- Glass patterns
- Finish



Calculations

Maximum allowable width of unit = 72

Maximum allowable height of unit = 72

Glass Size

Width = (Unit Width ÷ 3) - 7/8

Height = Unit Ht. - 4

Metal Cuts

SC-559 Track filler (optional) = Unit width - 1/4

SC-560 tub track = Unit width - 1/4

SC-561 wall jamb = Unit ht. - 1 5/8

SC-562 side rail = Unit ht. - 2 7/8

SC-563 bottom rail = (Unit width ÷ 3) - 1 1/2

SC-564 top rail = (Unit width ÷ 3) - 1 1/2

SC-565 header = Unit width - 1/16

940/950 Parts List

- A. 1 Tub Track
- B. 2 Wall Jamb
- C. 1 Tub Track Filler
- D. 6 Plastic Wall Anchors
- E. 6 #8 x 1 1/2 Truss Head Screws
- F. 1 Header
- G. 1 Interior Glazed Door Panel
- H. 1 Center Glazed Door Panel
- J. 1 Exterior Glazed Door Panel
- K. 1 5/64 Allen Wrench
- L. 6 #6 x 7/16 Allen Head Set Screws
- M. 1 Vinyl Panel Splash Guard
- N. 1 Vinyl Panel Silencer
- P. 6 Pull Handles
- R. 12 #6 x 3/4 Truss Head Screws
- S. 6 Slot Covers
- T. 4 Clear Jamb Bumpers
- U. 2 Vinyl Drip Deflectors

